

SECTION 32 17 23 – PAVEMENT MARKINGS

PART 1 – GENERAL

1.01 WORK INCLUDED

- A. Marking of pavement including surface preparation and painting on bituminous or concrete surface.

1.02 ACCEPTANCE PROCEDURE

- A. Typical Sample Analysis
- B. Certification that paint meets requirements.

PART 2 – PRODUCTS

2.01 READY-MIXED PAINT

- A. Paint: Porter traffic paint, colors as follows:
 - 1. Parking lines and directional arrows: White
 - 2. No Parking areas: White
 - 3. Fire Lane: Yellow
 - 4. Handicapped Symbols: Blue and White
- B. Substitutions: Materials of the same function and performance are acceptable under provisions defined in Division 1 of the Specifications.

PART 3 – EXECUTION

3.01 INSTALLATION

- A. Prepare surface and apply paint with provisions of consistent agitation of paint with guns capable of applying a solid consistent marking.
- B. Apply paint markings to have true, sharp edges and ends, with lines of correct lengths, widths, and curvatures. Paint application to be performed in accordance with manufacturer's recommendations.
- C. Protection:
 - 1. Take precautions necessary to insure that paint does not soil adjacent surfaces.
 - 2. Place warning signs and traffic cones or similar devices to protect markings from being tracked by pedestrians or vehicles.
 - 3. Efface any tracked paint from adjacent areas and repair pavement markings.

END OF SECTION