Printing date 07/31/2016

Reviewed on 07/31/2016

## **1** Identification

- · Product name
- · Trade name: <u>Diethylzinc, min. 95%</u>
- Item number: 93-3030
- · CAS Number:
- 557-20-0 • **EC number:**
- 209-161-3 • Index number:
- 030-004-00-8
- Details of the supplier of the safety data sheet • Manufacturer/Supplier: Strem Chemicals, Inc.
- 7 Mulliken Way NEWBURYPORT, MA 01950 USA info@strem.com
- · Information department: Technical Department
- *Emergency telephone number: EMERGENCY: CHEMTREC: + 1 (800) 424-9300 During normal opening times: +1 (978) 499-1600*

## 2 Hazard(s) identification

· Classification of the substance or mixture

GHS02 Flame

Flam. Liq. 2H225 Highly flammable liquid and vapor.Pyr. Liq. 1H250 Catches fire spontaneously if exposed to air.Water-react. 1H260 In contact with water releases flammable gases, which may ignite spontaneously.

GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

· Label elements

· GHS label elements

The substance is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Danger

- Hazard-determining components of labeling: diethylzinc
- Hazard statements H225 Highly flammable liquid and vapor.

(Contd. on page 2)

<sup>-</sup> US

Printing date 07/31/2016

CHEMICALS, INC.

Reviewed on 07/31/2016

Trade name: Diethy	ade name: Diethylzinc, min. 95%	
	(Contd. of page 1)	
H250 Catches fi	re spontaneously if exposed to air.	
	with water releases flammable gases, which may ignite spontaneously.	
	vere skin burns and eye damage.	
· Precautionary s		
P231+P232	Handle under inert gas. Protect from moisture.	
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.	
P305+P351+P.	338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present	
	and easy to do. Continue rinsing.	
P403+P233	Store in a well-ventilated place. Keep container tightly closed.	
P422	Store contents under inert gas.	
P501	Dispose of contents/container in accordance with local/regional/national/international	
	regulations.	
· Classification s		
· NFPA ratings (		
The substance d • HMIS-ratings ( HEALTH 3 FIRE 4 REACTIVITY 2 • Other hazards	Health = 3 Fire = 4 Reactivity = 2 and vPvB assessment cable.	
3 Composition	information on ingredients	
Chemical chara CAS No. Descru 557-20-0 diethy Identification n EC number: 20 Index number:	zinc umber(s) 9-161-3	
• CAS No. Descri 557-20-0 diethy • Identification n • EC number: 20	ption Izinc umber(s) 9-161-3 030-004-00-8	

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:

• Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

US

Printing date 07/31/2016

Reviewed on 07/31/2016

Trade name: Diethylzinc, min. 95%

• *Indication of any immediate medical attention and special treatment needed No further relevant information available.* 

#### **5** Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- Sand. Do not use water.
- CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- $\cdot$  Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

### 6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.
- Environmental precautions:
- Do not allow product to reach sewage system or any water course.
- Prevent seepage into sewage system, workpits and cellars.
- Inform respective authorities in case of seepage into water course or sewage system.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent.
  - Dispose contaminated material as waste according to item 13.
  - Ensure adequate ventilation.
- Do not flush with water or aqueous cleansing agents
- Reference to other sections See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

### 7 Handling and storage

- Handling: Handle under inert gas.
- Precautions for safe handling
   Ensure good ventilation/exhaustion at the workplace.
   Open and handle receptacle with care.
   Prevent formation of aerosols.
   Information about protection against explosions and fires:
- Keep ignition sources away Do not smoke.
- Protect against electrostatic charges. Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage: Store contents under inert gas.
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.

(Contd. on page 4)

US

(Contd. of page 2)

Printing date 07/31/2016

Reviewed on 07/31/2016

Trade name: Diethylzinc, min. 95%

• Further information about storage conditions: Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

• Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace: Not required.

- Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

# 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form:

Liquid

(Contd. on page 5)

US

(Contd. of page 3)

Printing date 07/31/2016

CHEMICALS, INC.

Reviewed on 07/31/2016

		(Contd. of page
Color:	Colorless	
· Odor:	Unpleasant	
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
Melting point/Melting range:	-28 °C (-18 °F)	
Boiling point/Boiling range:	124 °C (255 °F)	
· Flash point:	-18 °C (-0 °F)	
· Flammability (solid, gaseous):	Not determined.	
· Ignition temperature:		
Decomposition temperature:	Not determined.	
· Auto igniting:	Spontaneously flammable in air.	
· Danger of explosion:	Not determined.	
· Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapor pressure at 20 °C (68 °F):	121 hPa (91 mm Hg)	
• Density at 20 •C (68 •F):	1.18 g/cm <sup>3</sup> (9.847 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
$\cdot$ Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wate	<b>r</b> ): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	0.0 %	
VOC content:	0.0 g/l / 0.00 lb/gl	
• Other information	No further relevant information available.	

# 10 Stability and reactivity

· **Reactivity** No further relevant information available.

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· Possibility of hazardous reactions No dangerous reactions known.

· Conditions to avoid No further relevant information available.

· Incompatible materials: No further relevant information available.

· Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 6)

US

Printing date 07/31/2016

Reviewed on 07/31/2016

Trade name: Diethylzinc, min. 95%

(Contd. of page 5)

### **11 Toxicological information**

- · Information on toxicological effects
- Acute toxicity:
- Primary irritant effect:
- on the skin: Caustic effect on skin and mucous membranes.
- on the eye: Strong caustic effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

Substance is not listed.

· NTP (National Toxicology Program)

Substance is not listed.

· OSHA-Ca (Occupational Safety & Health Administration)

Substance is not listed.

#### **12 Ecological information**

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- · Additional ecological information:
- · General notes: Must not reach bodies of water or drainage ditch undiluted or unneutralized.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

#### **13 Disposal considerations**

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

4 Transport information		
· UN-Number		
· DOT, IMDG, IATA	UN3394	

Printing date 07/31/2016

CHEMICALS, INC.

Reviewed on 07/31/2016

	(Contd. of pag
UN proper shipping name	
DOT	Organometallic substance, liquid, pyrophoric, water-reacti
IMDG	(diethylzinc) ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORI
	WATER- REACTIVE (diethylzinc)
IATA	Organometallic substance, liquid, pyrophoric, water-reactive
Transport hazard class(es)	
DOT	
Class	4.2 Substances liable to spontaneous combustion
Label	4.2, 4.3
IMDG	
Class	4.2 Substances liable to spontaneous combustion
Label	4.2/4.3
Class	4.2 Substances liable to spontaneous combustion
Label	<i>4.2 Substances hable to spontaneous combustion</i> <i>4.2 (4.3)</i>
Packing group DOT, IMDG, IATA	Ι
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Not applicable.
Danger code (Kemler): EMS Number:	X333 F-G,S-M
Stowage Category	D
Handling Code	H1 Keep as dry as reasonably practicable
Segregation Code	SG26 In addition: from goods of classes 2.1 and 3 when stowed
	deck of a containership a minimum distance of two container spac athwartship shall be maintained, when stowed on ro-ro ships
	distance of 6 m athwartship shall be maintained.
	SG35 Stow "separated from" acids.
	SG63 Stow "separated longitudinally by an intervening comple
	compartment or hold from" Class 1.
Transport in bulk according to Ann	_

US

Printing date 07/31/2016

CHEMICALS, INC

Reviewed on 07/31/2016

Trade name: Diethylzinc, min. 95%

	(Contd. of page 7
· Transport/Additional information:	
·DOT	
• Quantity limitations	On passenger aircraft/rail: Forbidden
	On cargo aircraft only: Forbidden
· IMDG	
$\cdot$ Limited quantities (LQ)	0
$\cdot$ Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 3394 ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE (DIETHYLZINC), 4.2 (4.3), I

## **15 Regulatory information**

Safety, health and environmental regulations/legislation specific for the substance or mixture
 Sara
 Section 355 (extremely hazardous substances):

Substance is not listed.

· Section 313 (Specific toxic chemical listings):

Substance is listed.

· TSCA (Toxic Substances Control Act):

Substance is listed.

· Proposition 65

· Chemicals known to cause cancer:

Substance is not listed.

· Chemicals known to cause reproductive toxicity for females:

Substance is not listed.

· Chemicals known to cause reproductive toxicity for males:

Substance is not listed.

· Chemicals known to cause developmental toxicity:

Substance is not listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

557-20-0 diethylzinc

• TLV (Threshold Limit Value established by ACGIH)

Substance is not listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

Substance is not listed.

· GHS label elements

The substance is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 9)

D, I, II

US –

Printing date 07/31/2016

Reviewed on 07/31/2016

	(Contd. of pa
· Hazard pictogra	
	The second s
<u><u></u></u>	
GHS02 GHS	505
Signal word Da	
· Signal word Da	nger
· Hazard-determi	ining components of labeling:
diethylzinc	
· Hazard stateme	nts
H225 Highly fla	mmable liquid and vapor.
H250 Catches fi	ire spontaneously if exposed to air.
H260 In contact	t with water releases flammable gases, which may ignite spontaneously.
H314 Causes se	vere skin burns and eye damage.
· Precautionary s	tatements
P231+P232	Handle under inert gas. Protect from moisture.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P305+P351+P.	338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if pre
	and easy to do. Continue rinsing.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P422	Store contents under inert gas.
P501	Dispose of contents/container in accordance with local/regional/national/internation regulations.
	rogulations

# **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Technical Department.
- · Contact: Technical Director
- · Date of preparation / last revision 07/31/2016 / -
- · Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit **REL:** Recommended Exposure Limit Flam. Liq. 2: Flammable liquids, Hazard Category 2 Pyr. Liq. 1: Pyrophoric Liquids, Hazard Category 1 Water-react. 1: Substances and Mixtures which, in contact with water, emit flammable gases, Hazard Category 1 Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B